Google

Checkout

mail server receive probing result from the recip | Search

Web Results 1 - 10 of about 288,000 for **mail server receive probing result from the recipient**. (0.29 seconds)

Postfix Address Verification

This is SAFE because the Postfix SMTP **server** does not reject **mail** for ... If a **recipient probe** fails, then Postfix rejects **mail** for the **recipient** address. ...
www.postfix.org/ADDRESS_VERIFICATION_README.html - 22k - Cached - Similar pages

Mail Exchangers MX SMTP email domain

Since your **email** is not personally addressed to each and every **recipient**, a **mail server** that **received** such **email** may automatically filter and identify it as ...
www.**mails**broadcast.com/**email**.broadcast.faq/5.faq.**mailserver**.htm - 46k - Cached - Similar pages

Postfix Address Verification

If a **recipient probe** fails, then Postfix rejects **mail** for the **recipient** address. ... To avoid **probing** the same address repeatedly, you can store the **result** ...
netmirror.org/mirror/postfix.org/ADDRESS_VERIFICATION_README.html - 23k
- Cached - Similar pages

[NOT SUBMITTED YET!!!] INTERNET-DRAFT Grant Neufeld draft-neufeld ...

The drawback to this approach is that valid **recipients** will **receive** the **probe** messages in their **mail** - an unfortunate waste of time and resources. ...
www.nisto.com/listspec/ietf/draft-neufeld-list**probe**-00.txt - 6k - Cached - Similar pages

Shortest-Path Mailing Service Using Active Technology

must transmit **mail** to **recipient**'s **mail server** via the sender's **mail server**. .... send **probing received** reply packet (type=5) to the previous node of active ...
www.springerlink.com/index/28vnu8me0bu95674.pdf - Similar pages

Enterprise Software and Message Resources on TechRepublic

Once a message is downloaded from the e-**mail server**, the default setting is to ... Designed for **probing**, prospecting with power dialing (caller presses ...
search.techrepublic.com.com/search/Enterprise+Software+and+Message.html - 63k
- Cached - Similar pages

[PDF] ioMail Acceptable Use Policy Page 1 of 2 Acceptable Use Policy

File Format: PDF/Adobe Acrobat - View as HTML
Send **email** messages which **result** in complaints from the **recipient** or from ... or which **result** in blacklisting of the sender's **email** address or **mail server** ...
www.iomail.com.au/ioMail_AUP.pdf - Similar pages

Pixel Acres » Blog Archive » Securing PHP Contact Forms

We have hard coded the **recipient's email** address in PHP, so it would be natural **...** fields for line breaks, you may still **receive** a spammer's **probe** emails. **...**
f6design.com/journal/2006/12/09/securing-php-contact-forms/ - 25k - Cached - Similar pages

Dovetail Internet [Authorized Use Policy (AUP)] - Network ...

Send **email** messages which **result** in complaints from the **recipient** or **...** or **mail server**, or negatively impacts other customers who use the **Email** Services. **...**
www.dovetailinternet.com/AUP/ - 10k - Cached - Similar pages

Главная

If a **recipient probe** fails, then Postfix rejects **mail** for the **recipient** address. **...** address verification **results** before you start to actually reject **mail**. **...**
www.elantech.ru/docs/postfix-docs-ru/ADDRESS_VERIFICATION_README.html - 30k
- Cached - Similar pages

Goooooooooogle ▶

1 2 3 4 5 6 7 8 9 10 **Next**

| mail server receive probing result fr | | Search |

Search within results | **Language Tools** | **Search Tips** | **Dissatisfied? Help us improve** | **Try Google Experimental**

©2008 Google - **Google Home** - **Advertising Programs** - **Business Solutions** - **About Google**